

पेटेंट कार्यालय का एक प्रकाशन
PUBLICATION OF THE PATENT OFFICE

The Patent Office Journal No. 24/2022 Dated 17/06/2022

36815

(12) PATENT APPLICATION PUBLICATION

(21) Application No.202241033905 A

(19) INDIA

(22) Date of filing of Application :14/06/2022

(43) Publication Date : 17/06/2022

(54) Title of the invention : Experimental Investigation Of Effect Of Pitch Augmentation In Fluro Polymer Spiral Tube In Tube Heat Exchanger And Optimization Of Flow Parameter For Minimum Fouling

(51) International classification F28D0007020000, F28F0021060000, F28D0007100000, F28F0001000000, F28F0009013000
(86) International Application No PCT// Filing Date 01/01/1900
(87) International Publication No :NA
(61) Patent of Addition to Application Number :NA Filing Date :NA
(62) Divisional to Application Number :NA Filing Date :NA

(71)Name of Applicant :

1)Mr.S Krishnan

Address of Applicant :Associate Professor, Department of Mechanical Engineering, Dhurajal Gandhi College of Technology, Salem 636309, Tamilnadu, India Salem -----

2)Dr. P. Senthil Kumar

3)Mr. Kamalochan Barman

4)Ms. Bhanita Das

5)Dr. Sivakumar Ponnusamy

6)Dr. T Venkata Deepthi

7)Dr. Sudarshana Borah

Name of Applicant : NA

Address of Applicant : NA

(72)Name of Inventor :

1)Mr.S Krishnan

Address of Applicant :Associate Professor, Department of Mechanical Engineering, Dhurajal Gandhi College of Technology, Salem 636309, Tamilnadu, India Salem -----

2)Dr. P. Senthil Kumar

Address of Applicant :Professor & Head, Department of Mechanical Engineering, Dhurajal Gandhi College of Technology, opposite Salem Airport, Salem- 636309 Salem -----

3)Mr. Kamalochan Barman

Address of Applicant :Assistant Professor, School of Pharmaceutical Sciences, University of Science and Technology, Meghalaya- 793101 Techno City -----

4)Ms. Bhanita Das

Address of Applicant :Assistant Professor, School of Pharmaceutical Sciences, University of Science and Technology, Meghalaya- 793101 Techno City -----

5)Dr. Sivakumar Ponnusamy

Address of Applicant :Associate Professor, Department of Computer Science and Engineering, SRM Institute of Science and Technology, Delhi-NCR Campus, Delhi - Meerut Expy, Modinagar, Uttar Pradesh- 201204 Modinagar -----

6)Dr. T Venkata Deepthi

Address of Applicant :Associate Professor, Department of Mechanical Engineering, Malla Reddy Engineering College-Main Campus (Autonomous), Medchal, Secunderabad, Telangana 500100 Secunderabad -----

7)Dr. Sudarshana Borah

Address of Applicant :Assistant Professor, School of Pharmaceutical Sciences, University of Science and Technology Meghalaya-793101 Techno City -----

(57) Abstract :

In-process and chemical industry applications, chemically inert and non-corrosive heat exchangers are required to ensure no contamination and less fouling, even though conventional heat exchangers are made of copper, aluminum, and other metallic materials are rarely useful in these applications. Although polymeric materials heat exchangers are chemically inert, they do not have the thermal capacities necessary for use as heat exchangers. The fluro-polymer heat exchangers are the only polymeric heat exchangers with even a small heat transfer capacity compared to other types. Because the geometry of a heat exchanger is so important in defining its heat transfer capacities and fouling resistance, spiral tubes in tube heat exchangers are the most compact of the heat exchangers available. At the same time, the pumping power needed is somewhat greater. This heat exchanger design has a challenging manufacturing process, and it is also tough to clean over time for routine maintenance and inspection. The issue of fouling may be addressed in the manner indicated in our proposal, namely, by the inclusion of variable pitch, which alters the form geometry of the spiral by adjusting the pitch of the conical spiral, hence preventing scaling and fouling. The design and development of a heat exchanger are heavily influenced by the geometry of the tubes used in the process. Specifically, the development of a heat exchanger in which the fluro polymer tube is wound in a spiral shape and in which hot fluid is always passed from inside to the outside of the spiral, but the path of cold fluid can be changed to achieve the parallel flow or counter flow configuration is discussed in this invention.

No. of Pages : 23 No. of Claims : 4



Controller General of Patents, Designs and Trademarks
Department of Industrial Policy and Promotion
Ministry of Commerce and Industry

Design Application Details

Application Number:

363008-001

Cbr Number:

200900

Cbr Date:

23/04/2022 12:48:52

Applicant Name:

- 1. Ruhul Amin 2. Dr. Faruk Alam
- 3. Dr. Pallab Kalita
- 4. Gaurav Kumar Bhargav

Design Application Status

Application Status:

Application Accepted, Certificate of Design not Generated.

Back

Disclaimer: Application status is available for the application filed on or after 1st April 2009 with application no 222230. The information under " Design Application Status" is dynamically retrieved and is



Registrar
University of Science & Technology,
Meghalaya